

DECLARATION OF PERFORMANCE

N° MP3 01A EN



LR ETANCO SAS

Parc les Erables – Bât 1 – 66 route de Sartrouville – BP 49 – 78231 LE PECQ Cedex – France

Tel. : +33 (0)1 34 80 52 00 – Fax : +33 (0)1 30 71 01 89

E-mail : commercial.france@etanco.fr – Web : www.etanco.eu

1. Unique identification code of the product-type :

FM-MP3 EVO

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-09/0067 – ETA-10/0074
Batch number: see packaging of the product

3. Indented use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

ETA-09/0067	
Generic type and intended use of the product	Torque controlled expansion anchor made of galvanized steel, sizes M6, M8, M10 and M12
For use in	Un-cracked concrete (C20/25 to C50/60 according to EN 206-1:2003)
Option / category	ETAG 001 option 7
Loading	Static and quasi-static
Material	Steel class 8.8 according to EN ISO 898-1 Zinc-plated steel according to EN ISO 4042: Dry internal conditions only
Fire class	A1 according to EN 13501-1

ETA-10/0074	
Generic type and intended use of the product	Anchor made of galvanized steel multiple use for non-structural applications, sizes M6, M8, M10 and M12
For use in	Cracked and un-cracked concrete (C20/25 to C50/60 according to EN 206-1:2003)
Option / category	ETAG 001 part 6 + TR 020
Loading	Static and quasi-static, fire resistance
Material	Steel class 8.8 according to EN ISO 898-1 Zinc-plated steel according to EN ISO 4042: Dry internal conditions only
Fire class and resistance	A1 according to EN 13501-1 F120

4. Name, registered trade name or registered trade mark and contract address of the manufacturer as required pursuant to Article 11(5):

FRIULSIDER S.p.A.
Via Trieste 1
33048 San Giovanni al Natisone (UD)
Italy

5. Where applicable name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1 – ETA-09/0067
System 2+ – ETA-10/0074

DECLARATION OF PERFORMANCE

N° MP3 01A EN



7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Not relevant

8. In case of the declaration of performance concerning a construction product for which European Technical Assessment has been issued:

Z.A.G. approval body issued ETA-09/0067 on the basis of 'ETAG 001 part 2.

Z.A.G. notified body n°1404 issued according to system 1 the certificate of conformity n° 1404-CPD-1433.

Z.A.G. approval body issued ETA-10/0074 on the basis of 'ETAG 001 part 6.

Z.A.G. notified body n°1404 issued according to system 2+ the certificate of conformity n° 1404-CPD-1602.

9. Declared Performances:

ETA-09/0067					
Essential characteristics – ETAG 001 Annex C		Performance			
Installation parameters		M6 ²⁾	M8	M10	M12
d₀	Nominal diameter of drill bit [mm]	10	12	15	18
h_{nom}	Minimum installation depth [mm]	45	50	60	80
h_{ef}	Effective anchorage depth [mm]	36 ²⁾	43	50	69
h_{min}	Minimum thickness of the concrete member [mm]	100	100	100	140
T_{inst}	Nominal torque moment [Nm]	8	15	30	50
s_{min}	Minimum spacing [mm]	35	45	50	75
c_{min}	Minimum edge distance [mm]	35	45	50	75
Tension Steel failure mode					
N_{Rk,s}	Tension Steel characteristic failure [kN]	16	29	46	67
γ_{m,sN} ¹⁾	Partial safety factor for tension steel failure [-]	1,5			
Pull-out failure mode					
N_{Rk,p,ucr}	Tension characteristic load in un-cracked concrete [kN]	7,5 ²⁾	12	17,8 ³⁾	25 ³⁾
γ₂	Partial safety factor [-]	1,0			
γ_{m,c} ¹⁾	Partial safety factor [-]	1,5			
s_{cr,N}	Critical spacing [mm]	108	129	150	207
c_{cr,N}	Critical edge distance [mm]	54	65	75	104
ψ_c C30/37		1,22			
ψ_c C40/50	Increasing factor [-]	1,41			
ψ_c C50/60		1,55			
Splitting failure mode					
s_{cr,sp}	Critical spacing (splitting) [mm]	216	258	300	414
c_{cr,sp}	Critical edge distance (splitting) [mm]	54	65	75	104
γ_{m,c} ¹⁾	Partial safety factor [-]	1,5			
Displacement on Tension Load					
N_{ucr}	Service tension load in un-cracked concrete C20/25 [kN]	3,6	5,7	8,5	11,9
δ_{N0,ucr}	Short term displacement under tension load [mm]	0,12	0,11	0,27	0,37
δ_{N∞,ucr}	Long term displacement under tension load [mm]	0,95	0,95	0,95	0,95
Shear Steel failure mode					
V_{Rk,s}	Shear Steel characteristic failure [kN]	6,4	14,4	23,2	33,2
M⁰_{Rk,s}	Bending Moment characteristic failure [Nm]	12	30	60	105
γ_{m,sV} ¹⁾	Partial safety factor for shear steel failure [-]	1,25			
Shear Concrete Pry-out and Edge failure mode					
k	Factor equation (5.6) of ETAG, Annex C, § 5.2.3.3 [-]	1,0			2,0
l_{ef}	Effective anchorage length [mm]	36	43	50	69

Next 1

DECLARATION OF PERFORMANCE

N° MP3 01A EN



Next ↴

d_{nom}	Nominal diameter of anchor	[mm]	10	12	15	18
$\gamma_m^{1)}$	Partial safety factor ($\gamma_{m,c}=\gamma_{m,pr}$)	[-]	1,5			
Displacement on Shear Load						
V	Service shear load in concrete	[kN]	3,7	8,2	13,3	19,3
δ_{V0}	Short term displacement under shear load	[mm]	0,96	2,95	2,42	3,94
$\delta_{V\infty}$	Long term displacement under shear load	[mm]	1,40	4,42	3,63	5,91

¹⁾ In absence of other national regulations; ²⁾ Use restricted to anchoring of structural components statically indeterminated; ³⁾ Pull-out failure not decisive.

ETA-10/0074						
Essential Characteristics – ETAG 001 Annex C – TR 020			Performance			
All load directions			M6	M8	M10	M12
F_{Rk}^0	Characteristic load in concrete C20/25 to C50/60	[kN]	6	12	16	20
$\gamma_m^{1)}$	Partial safety factor	[-]	1,5			
F_{Rd}^0	Design load value in concrete C20/25 to C50/60	[kN]	4	8	10,6	13,3
F^0	Service load value in concrete C20/25 to C50/60	[kN]	2,9	5,7	7,6	9,5
S_{cr}	Critical spacing	[mm]	200	200	200	280
C_{cr}	Critical edge distance	[mm]	100	130	150	210
Shear load with lever arm						
$M_{Rk,s}^0$	Characteristic resistance	[Nm]	12	30	60	105
$\gamma_{m,s}^{1)}$	Partial safety factor	[-]	1,25			
Fire resistance* (all load direction)						
$F_{Rk,s,fi,30}$	For fire resistance duration = 30 minutes	[kN]	0,2	0,4	0,9	1,7
$F_{Rk,s,fi,60}$	For fire resistance duration = 60 minutes	[kN]	0,2	0,3	0,8	1,3
$F_{Rk,s,fi,90}$	For fire resistance duration = 90 minutes	[kN]	0,1	0,3	0,6	1,1
$F_{Rk,s,fi,120}$	For fire resistance duration = 120 minutes	[kN]	0,1	0,2	0,5	0,8

¹⁾ In absence of other national regulations.

We inform you that Friulsider is classified in the EC 1907/2006 Reach Directive as a Downstream-user of substances. The product supplied does not contain substances classified as SVHC according to the Candidate List in a concentration equal or greater than 0.1% (weight / weight). Article 31 is not applicable to the present product.

10. The performance of the product identified in points 1 and 2 is in conformity with declared performance in the point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Benoit Cheramy Product Manager	Le Pecq – France, 2013-06-21	
--	------------------------------	--