

DECLARATION OF PERFORMANCE

N° MP3A4 01A EN



LR ETANCO SAS

Parc les Erables – Bât 1 – 66 route de Sartrouville – BP 49 – 78231 LE PECQ Cedex – France

Tel. : +33 (0)1 34 80 52 00 – Fax : +33 (0)1 30 71 01 89

E-mail : commercial.france@etanco.fr – Web : www.etanco.eu

1. Unique identification code of the product-type :

FM-MP3 EVO A4

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

ETA-09/0357 – ETA-10/0093
Batch number: see packaging of the product

3. Indented use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

ETA-09/0357	
Generic type and intended use of the product	Torque controlled expansion anchor made of stainless steel, sizes M6, M8, M10 and M12
For use in	Un-cracked concrete (C20/25 to C50/60 according to EN 206-1:2003)
Option / category	ETAG 001 option 7
Loading	Static and quasi-static
Material	Stainless steel AISI316 grade A4-70 according to EN ISO 3506-1: internal dry conditions and external atmospheric exposure (including industrial and marine environment) or exposure in permanently damp internal conditions if no particular aggressive conditions exist.
Fire class	A1 according to EN 13501-1

ETA-10/0093	
Generic type and intended use of the product	Anchor made of stainless steel multiple use for non-structural applications, sizes M6, M8, M10 and M12
For use in	Cracked and un-cracked concrete (C20/25 to C50/60 according to EN 206-1:2003)
Option / category	ETAG 001 part 6 + TR 020
Loading	Static and quasi-static, fire resistance
Material	Stainless steel AISI316 grade A4-70 according to EN ISO 3506-1: internal dry conditions and external atmospheric exposure (including industrial and marine environment) or exposure in permanently damp internal conditions if no particular aggressive conditions exist.
Fire class and resistance	A1 according to EN 13501-1 F120

4. Name, registered trade name or registered trade mark and contract address of the manufacturer as required pursuant to Article 11(5):

FRIULSIDER S.p.A.
Via Trieste 1
33048 San Giovanni al Natisone (UD)
Italy

5. Where applicable name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 (2):

Not relevant

DECLARATION OF PERFORMANCE

N° MP3A4 01A EN



6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1 – ETA-09/0357
System 2+ – ETA-10/0093

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

Not relevant

8. In case of the declaration of performance concerning a construction product for which European Technical Assessment has been issued:

Z.A.G. approval body issued ETA-09/0067 on the basis of 'ETAG 001 part 2.
Z.A.G. notified body n°1404 issued according to system 1 the certificate of conformity n° 1404-CPD-1540.

Z.A.G. approval body issued ETA-10/0074 on the basis of 'ETAG 001 part 6.
Z.A.G. notified body n°1404 issued according to system 2+ the certificate of conformity n° 1404-CPD-1601.

9. Declared Performances:

ETA-09/0357						
Essential characteristics – ETAG 001 Annex C			Performance			
Installation parameters			M6 ²⁾	M8	M10	M12
d ₀	Nominal diameter of drill bit	[mm]	10	12	15	18
h _{nom}	Minimum installation depth	[mm]	45	50	60	80
h _{ef}	Effective anchorage depth	[mm]	36 ²⁾	43	50	69
h _{min}	Minimum thickness of the concrete member	[mm]	100	100	100	140
T _{inst}	Nominal torque moment	[Nm]	8	15	30	50
s _{min}	Minimum spacing	[mm]	35	45	50	75
c _{min}	Minimum edge distance	[mm]	35	45	50	75
Tension Steel failure mode						
N _{Rk,s}	Tension Steel characteristic failure	[kN]	14	25	40	69
γ _{m,sN} ¹⁾	Partial safety factor for tension steel failure	[-]	1,87			
Pull-out failure mode						
N _{Rk,p,ucr}	Tension characteristic load in un-cracked concrete	[kN]	6 ²⁾	12	16	25
γ ₂	Partial safety factor	[-]	1,2			
γ _{m,c} ¹⁾	Partial safety factor	[-]	1,8			
s _{cr,N}	Critical spacing	[mm]	108	129	150	207
c _{cr,N}	Critical edge distance	[mm]	54	65	75	104
ψ _c C30/37	Increasing factor	[-]	1,22			
ψ _c C40/50		[-]	1,41			
ψ _c C50/60		[-]	1,55			
Splitting failure mode						
s _{cr,sp}	Critical spacing (splitting)	[mm]	216	258	300	414
c _{cr,sp}	Critical edge distance(splitting)	[mm]	108	129	150	207
γ _{m,c} ¹⁾	Partial safety factor	[-]	1,8			
Displacement on Tension Load						
N _{ucr}	Service tension load in un-cracked concrete C20/25	[kN]	2,4	4,8	6,4	9,9
δ _{N0,ucr}	Short term displacement under tension load	[mm]	0,02	0,11	0,03	0,01
δ _{N∞,ucr}	Long term displacement under tension load	[mm]	0,95	0,95	0,95	0,95
Shear Steel failure mode						
V _{Rk,s}	Shear Steel characteristic failure	[kN]	7	12	20	29
M ⁰ _{Rk,s}	Bending Moment characteristic failure	[Nm]	10	26	52	91

DECLARATION OF PERFORMANCE

N° MP3A4 01A EN



$\gamma_{m,sV}^{1)}$	Partial safety factor for shear steel failure	[-]	1,55			
Shear Concrete Pry-out and Edge failure mode						
k	Factor equation (5.6) of ETAG, Annex C, § 5.2.3.3	[-]	1,0			2,0
l_{ef}	Effective anchorage length	[mm]	36	43	50	69

Next 1

Next 1

d_{nom}	Nominal diameter of anchor	[mm]	10	12	15	18
$\gamma_m^{1)}$	Partial safety factor ($\gamma_{m,c}=\gamma_{m,pr}$)	[-]	1,8			
Displacement on Shear Load						
V	Service shear load in concrete	[kN]	3,2	5,9	9,3	16,6
δ_{V0}	Short term displacement under shear load	[mm]	0,85	1,37	1,21	1,24
$\delta_{V\infty}$	Long term displacement under shear load	[mm]	1,28	2,06	1,82	1,86

¹⁾ In absence of other national regulations; ²⁾ Use restricted to anchoring of structural components statically indeterminated;

ETA-10/0093						
Essential Characteristics – ETAG 001 Annex C – TR 020			Performance			
All load directions			M6	M8	M10	M12
F _{Rk} ⁰	Characteristic load in concrete C20/25 to C50/60	[kN]	4	9	12	25
γ _m ¹⁾	Partial safety factor	[-]	1,5			1,8
F _{Rd} ⁰	Design load value in concrete C20/25 to C50/60	[kN]	2,7	6	8	13,9
F ⁰	Service load value in concrete C20/25 to C50/60	[kN]	1,9	4,3	5,7	9,9
s _{cr}	Critical spacing	[mm]	200	200	200	280
c _{cr}	Critical edge distance	[mm]	100	130	150	210
Shear load with lever arm						
M ⁰ _{Rk,s}	Characteristic resistance	[Nm]	10	26	52	91
γ _{m,s} ¹⁾	Partial safety factor	[-]	1,55			
Fire resistance* (all load direction)						
F _{Rk,s,fi,30}	For fire resistance duration = 30 minutes	[kN]	0,2	0,7	1,5	2,5
F _{Rk,s,fi,60}	For fire resistance duration = 60 minutes	[kN]	0,2	0,6	1,2	2,1
F _{Rk,s,fi,90}	For fire resistance duration = 90 minutes	[kN]	0,1	0,4	0,9	1,7
F _{Rk,s,fi,120}	For fire resistance duration = 120 minutes	[kN]	0,1	0,4	0,8	1,4

¹⁾ In absence of other national regulations.

We inform you that Friulsider is classified in the EC 1907/2006 Reach Directive as a Downstream-user of substances. The product supplied does not contain substances classified as SVHC according to the Candidate List in a concentration equal or greater than 0.1% (weight / weight). Article 31 is not applicable to the present product.

10. The performance of the product identified in points 1 and 2 is in conformity with declared performance in the point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Benoit Cheramy Product Manager	Le Pecq – France, 2013-06-21	
--	------------------------------	--