

## QUIK DRIVE® WATERPROOFING BELT SCREWING SYSTEM



### PRODUCT DEFINITION

- The QUIK DRIVE® belt screwing system is designed for fixing steel pans to metal frames and overlap fixing steel pans in a standing position.
- The nose of the tool allows for optimal placement of the tool in the corrugated of the waterproofing support pan
- The extension allows you to work standing up and thus reduce the arduousness at work.
- The fastening belts enable continuous automatic screwdriving and reduce the risk of losing fasteners on the construction site.
- Requires no lubrication (Teflon®).
- Possible positioning of the tool on the adapter and extension in 360°.
- Installation on the screwdriver or extension by simply clipping it on.
- Curved loading guide for faster belt insertion.

### SCOPE OF APPLICATION

- Fixing waterproofing support pans.
- Overlap fixing of waterproofing support pans.
- For Ø4.8, Ø5.5 and Ø6.3 mm screws.
- Screw lengths: 13 to 38 mm.

### MATERIAL & FINISH

#### Material:

- Steel and plastic tool
- Steel and aluminium extension and adapter.
- Yellow plastic tape (Low-Density Polyethylene - LDPE)

#### Finish:

- Teflon® on moving components.

### INSTALLATION

1. Attach the QUIK DRIVE® adapter to the screwdriver.
2. Snap the QUIK DRIVE® tool into the QUIK DRIVE® extension.
3. Assemble the two sets together.
4. Tighten the dial of the QUIK DRIVE® extension ( counter clockwise).
5. Insert the screw belt into the QUIK DRIVE® tool loader.
6. Adjust the adjustment arm on the QUIK DRIVE® tool to the length of the screw.
7. Adjust the screw drive depth using the ring on the QUIK DRIVE® tool.
8. Start the screwdriver (preferably in continuous mode).
9. Press down on the assembly to attach or sew the waterproofing support pan.

Note: Instruction manuals are included with the various QUIK DRIVE® elements, they should be referred to for proper use.

## PERFORMANCE

- 30% faster installation than a traditional installation.
- Reduction of arduousness at work: Stand-up installation with the QUIK DRIVE® extension.

## DIMENSIONS & CODES

### QUIK DRIVE® tools:

Designation	Cond.	Code
QUIK DRIVE KIT + FEIN ADAPTER + SMALL EXTENSION	1	605 960*
QUIK DRIVE KIT + FEIN ADAPTER + LARGE EXTENSION	1	605 961*
QUIK DRIVE KIT + HILTI ADAPTER + SMALL EXTENSION	1	605 962*
QUIK DRIVE KIT + HILTI ADAPTER + LARGE EXTENSION	1	605 963*
KIT PAR 3: QUIK DRIVE TOOL + SMALL EXTENSION + REPLACEMENT SOCKET	1	605 964
QUIK DRIVE® WATERPROOFING TOOL ONLY	1	605 950

\* Kits include: QUIK DRIVE tool, extension, adapter, replacement socket and carrying case.



### QUIK DRIVE® extensions:

Designation	Cond.	Code
SMALL EXTENSION 406 MM	1	605 953
LARGE EXTENSION 508 MM	1	605 954



### QUIK DRIVE® screwdriver adapters:

Designation	Cond.	Code
FEIN ASCS ADAPTER	1	605 956
FEIN ASCM & ABS ADAPTER	1	605 970
HILTI ST1800 ADAPTER	1	605 955



## QUIK DRIVE® Belt Screws:

Designation	Application	Technical sheet	Cond.	Code
BOX OF 40 BELTS 25 FASTOVIS FC-R2 4T TH8 ZBJ 4.8X17	Overlap fixing	284 110 - TDS n° 4127	1	284 133
BOX OF 30 BANDS 25 GOLDOVIS 1.5SF TH8 ZBJ 6.3X22	Overlap fixing	331 180 - TDS n° 4019	1	331 120
BOX OF 30 BELTS 25 GOLDOVIS 5 TH8 ZBJ 5.5X25	Structural fixing	331 150 - TDS n° 4357	1	331 121
BOX OF 30 BELTS 25 GOLDOVIS 6 TH8 ZBJ 6.3X22	Structural fixing	331 257 - TDS n° 4021	1	331 122
BOX OF 30 BELTS 25 GOLDOVIS 12 TH8 ZBJ 5.5X32	Structural fixing	331 210 - TDS n° 4022	1	331 123



## QUIK DRIVE® replacement parts:

Designation	Conditioning	Code
H8 QUIK DRIVE® REPLACEMENT SOCKET	1	605 951
QUIK DRIVE® REPLACEMENT CHUCK	1	605 952



## QUIK DRIVE® add-on accessories:

Designation	Conditioning	Code
CARRYING STRAP + SCREW POCKET	1	180 681
QUIK DRIVE® CARRYING CASE	1	605 957



## CONFORMITY

- QUIK DRIVE® TOOL: CE marking according to the Safety Directive for Machinery 2006/42/EC.
- Screws in belts: In accordance with French standard DTU 43.3.

## MARKING & LABELLING

- Packaging: QUIK DRIVE® + CODE.

## QUALITY CONTROL

- ISO 9001 certified quality management system according to the certificate in force.

Registration date: 27/01/2025 – Revision B

LR ETANCO is a member of:



LR ETANCO - Parc les Érables - Bât. 1 - 66 Route de Sartrouville  
78231 Le Pecq Cedex France - [www.etanco.eu](http://www.etanco.eu)

Tel: +33 (0)1 34 80 52 00 – [commercial.france@etanco.fr](mailto:commercial.france@etanco.fr)

**NOTE**

These products are intended for professional installers landlords whose the related service includes supply and installation. In accordance with rules and normative regulation, it's their responsibility to check that the use of these products is in conformity to themselves needs and their customers. They have to insure as well the adequacy of this material with their real operating conditions. The company excludes any guarantee for the use that does not respect these conditions. His responsibility is limited to the strict compliance with the specifications stipulated on the customer's purchase order. The guarantee is limited to the replacement of defective parts acknowledged by the Company's technical service, without workforce costs and travel expenses. It excludes material damage or physical injury and others direct or indirect damages, material or immaterial, which may result from defective parts including installation that not complying with the use for which they are designed and produced.

**Registration date: 27/01/2025 – Revision B**

LR ETANCO is a member of:

**LR ETANCO** - Parc les Érables - Bât. 1 - 66 Route de Sartrouville  
78231 Le Pecq Cedex France - [www.etanco.eu](http://www.etanco.eu)Tel: +33 (0)1 34 80 52 00 - [commercial.france@etanco.fr](mailto:commercial.france@etanco.fr)